



P3H-15-CLX

specifications

- Pneumatic clamp
- 1,000 lbs.- 3 ton compression force(adjustable)
- 15" L-R x 15" F-B fully guided heated platens
- 6" - 12" open daylight
- 10" bore clamp cylinder
- 6" stroke
- 64 IPM closing speed
- 64 IPM pressing speed
- 100 IPM opening speed
- Weight: 2,050 lbs.
- Dimensions: 45" w x 28" d x 44" h

features

- Low friction rods and bushings
- Built in lift truck tubes
- Class 10,000 clean room compatible
- ViewPoint control system including:
 - Allen Bradley SLC 5/03 programmable controller
 - PanelView 550 touch screen
 - Closed-loop control of clamp pressure (including load cell)
 - Closed-loop control of platen temperature
- Ammeters for heater burnout detection (not pictured)
- Yokagawa six channel chart recorder (not pictured) including:
 - Data collection of platen temperature
 - Data collection of clamp force



Wabash MPI

1569 Morris St., P.O. Box 298, Wabash, IN 46992-0298 USA

Phone: 260-563-1184 Fax: 260-563-1396

Email: wabashmpi@acscorporate.com, Internet: www.wabashmpi.com

All data subject to change without notice ©2019 Wabash MPI

ISO 9001:2015
Certified

